


SPRO



DHDVR12-B3

12 CHANNEL 4K DVR (CVI / TVI / AHD / CVBS / IP)



12 CHANNELS



HDMI



VGA



PTZ CONTROL



H.264



IPHONE & ANDROID
PHONE VIEWING



APPLE MAC
VIEWING



USB BACKUP



Key Features:

- 12 channel recording (8 channel BNC + 4 channel IP)
- H264+/H.264 video compression
- Up to 4K(8MP) recording
- 4K@7fps, 4MP@15fps, 1080P@25fps
- Supports up to 8MP on extra IP channels
- Supports "IP Audio over CAT5e" on extra IP channels
- Supports alarm over co-ax cable(compatible cameras required)
- Supports audio over co-ax cable(compatible cameras required)
- PTZ control over co-ax cable
- P2P (no port forwarding required)
- Smart phone/Windows/Apple Mac viewing
- Intelligent feature : Facial & Tripwire detection (BNC channel only)
- Audio : 1 in & 1 out
- ONVIF 2.4
- 4K HDMI (3840x2160) & VGA



SPECIFICATIONS

Model Number

DHDVR12-B3

Main Processor

Embedded processor

Operating System

Embedded LINUX

Video and Audio

Input

12 channel (8 x BNC + 4 x IP)

Standard

5 IN 1

8 channel CVI/TVI/AHD/CVBS

IP

4 channel (up to 8 Megapixel IP)

(continued)

(continued)

Analog Camera Input	8 Channel, BNC
HDCVI Camera	4K, 4MP, 1080P@25fps, 720P@50fps, 720P@25fps
AHD Camera	2MP@25fps, 720P@25fps
TVI Camera	2MP@25fps, 720P@25fps
CVBS Camera	PAL/NTSC
IP Camera Input	4 Channel (up to 8MP)
Audio In/Out	1/1, RCA
Two-way Talk	Reuse audio in/out, RCA

Display

Interface	1 HDMI, 1 VGA	
Resolution	HDMI	3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720, 1024×768
	VGA	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4/8/9/16	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	

Recording

Video/Audio Compression	H.264+/H.264	
Resolution	4K, 5MP, 4MP, 3MP, 1080P, 720P, 960H, D1, CIF, QCIF	
Record Rate	Main Stream	4K(7fps),5MP(12fps),4MP/3MP(15fps),1080P/720P/960H/D1/CIF/QCIF (25fps)
	Extra Stream	960H(1~15fps), D1/CIF/QCIF(1~25fps)
Bit Rate	1Kbps ~ 6144Kbps Per Channel	
Record Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop	
Record Interval	1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	

Video Detection


Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis

Playback & Backup

Sync Playback	1/4/9
Search Mode	Time/Date, MD & Exact search (accurate to second)

(continued)

Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network
Network	
Interface	1 RJ-45 port (1000M)
Network Functions	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android Phone
Interoperability	ONVIF 2.4
Storage	
Internal HDD	1 SATA port, up to 8TB
Auxiliary Interface	
USB Interface	2 ports(1 Rear), 1 USB 3.0 & 1 USB 2.0
RS485	1 port, For PTZ Control
General	
Power Supply	DC12V/2A
Power Consumption	<10W (without HDD)
Working Environment	-10°C ~+55°C / 0%~90%RH
Dimensions	Compact 1U, 260mm × 220mm × 40mm
Weight	1.6 KG(without HDD)



All specifications are subject to change without notice. Copyright © Luxrite Ltd. All rights reserved